



ADVANTAGES

Precise control of width setting. Tensionless treatment. Even and powerful steaming.
 Speed :
 -Folding up to 40 m/min
 -Reproduction of treatment thanks to the display of all the parameters.
 Asynchronous motors driven by inverter.

Description

A	J storage box with automatic feeding
B	2 motorized moving feeding wheels with adjustable speed
C	Magnetic stretcher
D	Vertical steam box
E	2 shrinkage units
F	Connection conveyor
G	Cooling conveyor
H	Residual moisture suction group
I	Feeders
J	Folding head
K	Tossing pads maintaining the fabric in position
L	Automatic cardboard pushing device
M	Cardboard storage
N	Folding table with automatic downward movement
O	Evacuation conveyor

For an optimum dimension stability equipped with NON-STOP precision folding

Technical Data

Dimensions :	Machine supplied with
Length : 8,21 m	magnetic stretcher
Width : 2,76 m	Fold length : 580 to 800 mm
Height : 2,95 m	Maximum stack height : 540 mm
Weight : 5000 kg	Working width :
Electric power to be installed :	1300 mm or 1500 mm
10 kW without optional devices	Speed : up to 40m/min
Compressed air consumption :	
0,3 cu. m at 6 bar	
Steam consumption :	
60 to 80 kg/h according to fabric	
Cylinders maxi. Temperature : 150 °C	

KNITCOMPACT
 (PLIMATIC independant)
 NON-STOP

